



Fuel Consumption (ISO3046/1)	100% of Rated Load	90% of Rated Load	75% of Rated Load	50% of Rated Load
Fuel Consumption (LHV) ISO3046/1, kW (MMBTU/hr) ^{1,2,3,4}	3776 (12.89)	3435 (11.73)	2923 (9.98)	2064 (7.05)
Electrical Efficiency ISO3046/1, percent ^{1,2,4}	37.1%	36.7%	35.9%	33.9%
Thermal Efficiency ISO3046/1, percent ^{1,2,3,4}	50.4%	50.9%	51.2%	52.0%

Engine Data

Engine Manufacturer	Cummins
Engine Model	QSK60G – V16
Fuel Type	Natural Gas (Pipeline)
Displacement, L (cu.in)	60 (3672)
Aspiration	Turbocharged ¹
Gross Engine Power Output, kWm (hp)	1443 (1935)
Compression Ratio	11.4:1
Bore, mm (in)	159 (6.25)
Stroke, mm (in)	190 (7.48)
Rated Speed, rpm	1800
Piston Speed, m/s (ft/min)	11.4 (2244)
Lube Oil Capacity, L (qt)	379 (400)
Full Load Lubricating oil consumption, g/kWe-hr (g/hp-hr)	0.15 (0.11)
Electric starter voltage, volts	24
Min. Battery Capacity@40°C (104°F), AH	450

Fuel System

Gas supply pressure to engine inlet, bar (psi) ⁴	0.20-0.46 (2.9-6.7)
Min. Methane Index	78

Methane Number Capability

Load (Percent of Reted)			
100%	90%	75%	50%
78	69	54	45

* Technical drawing has given as a reference, Aksa reserves the right to make change in the model, technical specifications, color, equipment, accessories and images without prior notice.



Genset Dimensions – Open

Genset Length, m (ft) ⁵	5.0 (16.40)
Genset Width, m (ft) ⁵	2.33 (7.64)
Genset Height, m (ft) ⁵	2.97 (9.74)
Genset Weight (wet), kg (lbs) ⁵	13924 (30697)

Notes:

1. At ISO3046 reference conditions, altitude 1013 mbar (30 in Hg), air inlet temperature 25°C (77°F).
2. According to ISO 3046/I with fuel consumption tolerance of +5% -0%.
3. With air intake at 25°C (77°F). Tolerance $\pm 5^\circ\text{F}$.
4. Tested using pipeline natural gas with LHV of 33.44 MJ/Nm³ (905 BTU/ft³).
5. Weights and set dimensions represent a generator set with its standard features only.

Energy Data

	100% of Rated Load	90% of Rated Load	75% of Rated Load	50% of Rated Load
Continuous Generator Electrical Output kW _e @1.0pf ¹	1400	1260	1050	700
Continuous Shaft Power, kW _m (bhp) ^{1,2}	TBD	TBD	TBD	TBD
Total Heat Rejected in LT Circuit, kW (MMBTU/h) ³	102 (0.35)	92 (0.32)	84 (0.29)	68 (0.23)
Total Heat Rejected in HT Circuit, kW (MMBTU/h) ³	925 (3.16)	846 (2.89)	710 (2.42)	497 (1.69)
Unburnt, kW (MMBTU/h) ⁴	114 (0.39)	106 (0.36)	93 (0.32)	68 (0.23)
Heat Radiated to Ambient, kW (MMBTU/h) ⁴	162 (0.55)	147 (0.50)	125 (0.43)	87 (0.30)
Available Exhaust heat to 120C, kW (MMBTU/h) ³	980 (3.34)	902 (3.08)	787 (2.69)	576 (1.97)

Intake Air Flow

	100% of Rated Load	90% of Rated Load	75% of Rated Load	50% of Rated Load
Intake Air Flow Mass, kg/s (lb/hr) ⁵	2.37 (18817)	2.14 (16961)	1.81 (14342)	1.28 (10183)
Intake Air Flow Volume, m ³ /s @ 0°C (scfm) ⁵	1.83 (4090)	1.65 (3690)	1.40 (3130)	0.99 (2210)

Exhaust Air Flow

	100% of Rated Load	90% of Rated Load	75% of Rated Load	50% of Rated Load
Exhaust Gas Flow Mass, kg/s (lb/hr) ⁵	2.46 (19486)	2.21 (17569)	1.87 (14862)	1.33 (10556)
Exhaust Gas Flow Volume, m ³ /s (cfm) ⁵	5.25 (11120)	4.77 (10100)	4.10 (8680)	3.00 (6350)
Exhaust Temperature After Turbine, °C (°F) ⁶	482 (900)	488 (910)	501 (934)	524 (975)
Max Exhaust System Back Pressure, mmHG (inH ₂ O) ^{6,7}	37.3 (20.0)	37.3 (20.0)	37.3 (20.0)	37.3 (20.0)

HT Cooling Circuit

	100% of Rated Load	90% of Rated Load	75% of Rated Load	50% of Rated Load
HT Circuit Engine Coolant Volume, l (gal)	182 (48)	182 (48)	182 (48)	182 (48)
HT Coolant Flow @ Max Ext Restriction, m ³ /h (gal/min)	83 (365)	83 (365)	83 (365)	83 (365)
Max HT Engine Coolant Inlet Temp, °C (°F) Reference ⁸	79 (174)	80 (176)	82 (179)	84 (183)
HT Coolant Outlet Temp, °C (°F) ⁸	90 (194)	90 (194)	90 (194)	90 (194)
Max Pressure Drop in External HT Circuit, bar (psig)	1.5 (21.8)	1.5 (21.8)	1.5 (21.8)	1.5 (21.8)
HT Circuit Maximum Pressure, bar (psig)	4.5 (65)	4.5 (65)	4.5 (65)	4.5 (65)
Min Static Head, bar (psig)	0.5 (7)	0.5 (7)	0.5 (7)	0.5 (7)

* Technical drawing has given as a reference, Aksa reserves the right to make change in the model, technical specifications, color, equipment, accessories and images without prior notice.



LT Cooling Circuit

	100% of Rated Load	90% of Rated Load	75% of Rated Load	50% of Rated Load
LT Circuit Engine Coolant Volume, l (gal)	34 (9)	34 (9)	34 (9)	34 (9)
LT Coolant Flow @ Max Ext Restriction, m ³ /h (gal/min)	23 (101)	23 (101)	23 (101)	23 (101)
Max. LT Engine Coolant Inlet Temperature °C (°F) 9	54 (122)	50 (32)	50 (32)	50 (122)
Nominal LT Coolant Outlet Temperature °C (°F) 9	54 (129)	54 (32)	54 (32)	54 (129)
Max Pressure Drop in External LT Circuit, bar (psig)	1.0 (14.5)	1.0 (14.5)	1.0 (14.5)	1.0 (14.5)
LT Circuit Max Pressure, bar (psig)	4.5 (65)	4.5 (65)	4.5 (65)	4.5 (65)
Min Static Head, bar (psig)	0.5 (7)	0.5 (7)	0.5 (7)	0.5 (7)

Emissions

NO _x emissions, mg/Nm ³ @ 5% O ₂ (g/hp-h)	This rating is EPA NSPS Certified. Please refer to EPA emissions datasheet for regulation limits.
CO Emissions Rate mg/Nm ³ @5%O ₂ (g/hp-h)	
THC Exhaust Emissions, mg/Nm ³ @ 5% O, (g/hp-h)	

Alternator Data ¹⁰

Manufacturer	Mecc Alte
Alternator Made and Model	ECO 46 1S/4A
Frequency (Hz)	60
Power (kVA)	1800
Voltage (V)	480
Phase 3	3
A.V.R.	DER1
Voltage Regulation	(+/-)0.5%
Insulation System	H
Protection	IP23
Weight comp. Generator (kg)	3010
Cooling Air (m ³ /min)	162

Notes:

1. With engine driven coolant pump.
2. At ISO3046 reference conditions, altitude 1013 mbar (30 in Hg), air inlet temperature 25°C (77°F).
3. Production variation/tolerance ±10%.
4. Tolerance +/- 15%.
5. According to ISO 3046/I with fuel consumption tolerance of +5% -0%.
6. With air intake at 25°C (77°F). Tolerance ± 5°F
7. Exhaust system back pressure is a rated load and will decrease at lower loads.
8. Outlet temperature controlled by thermostat, inlet temperature for reference only.
9. Inlet temperature controlled by thermostat, outlet temperature for reference only.
10. Continuous (C)

Continuous rating definition

Applicable for supplying power continuously to a constant load up to the full output rating for unlimited hours. No sustained overload capability is available for this rating. Consult authorized distributor for rating (equivalent to continuous power in accordance with ISO8528, ISO3046, AS2789, DIN6271, and BS5514). This rating is not applicable to all generator set models.

* Technical drawing has given as a reference, Aksa reserves the right to make change in the model, technical specifications, color, equipment, accessories and images without prior notice.